

1317 Route 73 • SUITE 206 • MOUNT LAUREL, NJ 08054 • (888) 677-6906 • FAX: (856) 672-4283

WINTERIZATION CERTIFICATION				
TO:			DATE:	
COMPAN	NY:		FROM:	
FAX NU	MBER/EI	MAIL ADDRESS:	AMG CASE NO.:	
		PLEASE CO	OMPLETE AND FAX/EMAIL BACK	
SEL	LER	OWNER:		
		UMBER:		
		TY ADDRESS:		
		ATE, ZIP:		
CII	1,01	A112, 211.		
Please NPR (note the Proper Freezin Proper Capital able an Cos	ne following criteria: tty is vacant ng temperatures (32° F) and tty is assigned during the value of the List d comprehensive winteriz T OF WINTERIZATION I province to the PRE to respective NPRE	re expected to occur within the next 30 days winter months. Please complete IMMEDIATELY. Sing Agent follows the attached "Winterization Procedures" to guarantee an eation. See page 2 (Form 5). S NOT TO EXCEED \$150.00 Capital representative required for any winterization invoice that exceeds \$150.00. HELD LIABLE FOR ALL WINTERIZATION DECISIONS	
Please Select One:				
	Chec		has been winterized as specified on the attached Winterization Procedures pital Asset Management, LLC. Completed checklist must be returned with	
	the th	Gas/Electric/Propane/V The plumbing has been w "Wet" or "Dry" System.	e property has a heating system that is in acceptable working condition and° Fahrenheit and ALL of the following items are true: Water service(s) are set up to provide necessary fuel for heating system. winterized in accordance with the Winterization Procedures Checklist for a bi-weekly property inspections to make sure that the heating system remains	
	Listin	ly indicate selection): I have confirmed that the	e property does not need winterization due to one of the following reasons the property was winterized by a prior company within the last year. Please terizing company below and date completed, if available.	
		Company Name:	Date:	
	0	*winterization not applied Due to local weather confreezing for an extended damages which may occur	ondition/annual season, the temperatures are not expected to reach below ed period of time. Listing Broker accepts full responsibility for any/all	
		winterization. Listing Br this decision. ng Broker Name: (Please Print)	roker accepts full responsibility for any/all damages which may occur due to	
		Signature: Date Signed:		
		Date Signed:		

NPR Asset Management, LLC ("NPR") is not the owner of the above referenced property and is acting solely as agent of the above named Seller/Owner. All services performed by real estate agents or any other third party vendors (collectively "Service Provider") are being performed strictly for and on behalf of said Seller/Owner. Invoices for services rendered are merely processed by NPR on behalf of the Seller/Owner and responsibility for payment lies with said Seller/Owner. As such, NPR Asset Management is not liable for any payments for services rendered hereunder. By agreeing to perform any service in connection with a property referred to hereunder, Service Provider acknowledges the foregoing.

NPR Asset Management, LLC.

1317 Route 73•SUITE 206•MOUNT LAUREL, NJ 08054•(888)677-6906•FAX: (856)672-4283

Winterization Procedures Checklist

Contact utility company; have water shut off at street. Listing broker's responsibility Shut off water valves(s) entering the property. Drain water from toilet tank(s) and bowls(s). Drain and blow air using air pressure; make sure ALL domestic water lines are clear. Includes ANY of the following (if present): all hot and cold water lines, hot water heater, water softener tank, brine tank, well water storage tank and/or the well water captive air bank, radiators, hot-water baseboards, and dishwasher. Add an appropriate amount of Propylene Glycol (non-toxic) to plumbing system and boiler Tape furnace switch and breaker to "Off" position. If water is supplied by a well: Tape off breaker panel Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) If a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. Install backflow prevention valve (as necessary).	Contact utility company; have water shut off at street. Listing broker's responsibility Shut off water valves(s) entering the property. Drain water from toilet tank(s) and bowls(s). Drain and blow air using air pressure; make sure ALL domestic water lines are clear. Includes ANY of the following (if present): all hot and cold water lines, hot water heater, water softener tank, brine tank, well water storage tank and/or the well water captive air bank, radiators, hot-water baseboards, and dishwasher. Add an appropriate amount of Propylene Glycol (non-toxic) to plumbing system and boiler Tape furnace switch and breaker to "Off" position. If water is supplied by a well: Turn well off at breaker panel Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) If a separate hot water tank is part of the hot water heating system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler.	1. Heat OFF	Domestic Plumbing with ANY TYPE of Heat System – "Wet" or "Dry" * *includes hot water baseboard, electric, forced air, or other system
Shut off water valves(s) entering the property. Drain water from toilet tank(s) and bowls(s). Drain and blow air using air pressure; make sure ALL domestic water lines are clear. Includes ANY of the following (if present): all hot and cold water lines, hot water heater, water softener tank, brine tank, well water storage tank and/or the well water captive air bank, radiators, hot-water baseboards, and dishwasher. Add an appropriate amount of Propylene Glycol (non-toxic) to plumbing system and boiler Tape furnace switch and breaker to "Off" position. If water is supplied by a well: Turn well off at breaker panel Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) If a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler.	Shut off water valves(s) entering the property. Drain water from toilet tank(s) and bowls(s). Drain and blow air using air pressure; make sure ALL domestic water lines are clear. Includes ANY of the following (if present): all hot and cold water lines, hot water heater, water softener tank, brine tank, well water storage tank and/or the well water captive air bank, radiators, hot-water baseboards, and dishwasher. Add an appropriate amount of Propylene Glycol (non-toxic) to plumbing system and boiler Tape furnace switch and breaker to "Off" position. If water is supplied by a well: Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) If a separate hot water tank is part of the hot water heating system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. Install backflow prevention valve (as necessary). Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		·
Drain water from toilet tank(s) and bowls(s). Drain and blow air using air pressure; make sure ALL domestic water lines are clear. Includes ANY of the following (if present): all hot and cold water lines, hot water heater, water softener tank, brine tank, well water storage tank and/or the well water captive air bank, radiators, hot-water baseboards, and dishwasher. Add an appropriate amount of Propylene Glycol (non-toxic) to plumbing system and boiler Tape furnace switch and breaker to "Off" position. If water is supplied by a well: Turn well off at breaker panel Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) If a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler.	Drain water from toilet tank(s) and bowls(s). Drain and blow air using air pressure; make sure ALL domestic water lines are clear. Includes ANY of the following (if present): all hot and cold water lines, hot water heater, water softener tank, brine tank, well water storage tank and/or the well water captive air bank, radiators, hot-water baseboards, and dishwasher. Add an appropriate amount of Propylene Glycol (non-toxic) to plumbing system and boiler Tape furnace switch and breaker to "Off" position. If water is supplied by a well: Turn well off at breaker panel Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) If a separate hot water tank is part of the hot water heating system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. Install backflow prevention valve (as necessary). Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		
Drain and blow air using air pressure; make sure ALL domestic water lines are clear. Includes ANY of the following (if present): all hot and cold water lines, hot water heater, water softener tank, brine tank, well water storage tank and/or the well water captive air bank, radiators, hot-water baseboards, and dishwasher. Add an appropriate amount of Propylene Glycol (non-toxic) to plumbing system and boiler Tape furnace switch and breaker to "Off" position. If water is supplied by a well: Turn well off at breaker panel Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) If a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler.	Drain and blow air using air pressure; make sure ALL domestic water lines are clear. Includes ANY of the following (if present): all hot and cold water lines, hot water heater, water softener tank, brine tank, well water storage tank and/or the well water captive air bank, radiators, hot-water baseboards, and dishwasher. Add an appropriate amount of Propylene Glycol (non-toxic) to plumbing system and boiler Tape furnace switch and breaker to "Off" position. If water is supplied by a well: Turn well off at breaker panel Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. Install backflow prevention valve (as necessary). Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		
Includes ANY of the following (if present): all hot and cold water lines, hot water heater, water softener tank, brine tank, well water storage tank and/or the well water captive air bank, radiators, hot-water baseboards, and dishwasher. Add an appropriate amount of Propylene Glycol (non-toxic) to plumbing system and boiler Tape furnace switch and breaker to "Off" position. If water is supplied by a well:	Includes ANY of the following (if present): all hot and cold water lines, hot water heater, water softener tank, brine tank, well water storage tank and/or the well water captive air bank, radiators, hot-water baseboards, and dishwasher. Add an appropriate amount of Propylene Glycol (non-toxic) to plumbing system and boiler Tape furnace switch and breaker to "Off" position. If water is supplied by a well: Tum well off at breaker panel Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) If a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. Install backflow prevention valve (as necessary). Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		
Tape furnace switch and breaker to "Off" position. If water is supplied by a well: Turn well off at breaker panel Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) IF a separate hot water tank is part of the hot water heating system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler.	Tape furnace switch and breaker to "Off" position. If water is supplied by a well: Turn well off at breaker panel Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) IF a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. Install backflow prevention valve (as necessary). Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		☐ Includes ANY of the following (if present): all hot and cold water lines, hot water heater, water softener tank, brine tank, well water storage tank and/or the well water captive air bank, radiators,
If water is supplied by a well: Turn well off at breaker panel Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) IF a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler.	If water is supplied by a well: Turn well off at breaker panel Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) If a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. Install backflow prevention valve (as necessary). Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		Add an appropriate amount of Propylene Glycol (non-toxic) to plumbing system and boiler
Turn well off at breaker panel Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) IF a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler.	Turn well off at breaker panel Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) IF a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. Install backflow prevention valve (as necessary). Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		Tape furnace switch and breaker to "Off" position.
□ Tape off breaker and disconnect power to the pump. □ Disconnect the line that supplies the water between the house and pressure tank □ Install a hose bib on the pressure tank side of the break □ Drain pressure tank □ Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) □ IF a separate hot water tank is part of the hot water heating system. □ Install a pipe to bypass domestic water system. □ Maintain water in heating system and put anti-freeze in to keep from freezing □ Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler.	Tape off breaker and disconnect power to the pump. Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) IF a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. Install backflow prevention valve (as necessary). Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		If water is supplied by a well:
 □ Disconnect the line that supplies the water between the house and pressure tank □ Install a hose bib on the pressure tank side of the break □ Drain pressure tank □ Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) □ IF a separate hot water tank is part of the hot water heating system. □ Install a pipe to bypass domestic water system. □ Maintain water in heating system and put anti-freeze in to keep from freezing □ Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. 	Disconnect the line that supplies the water between the house and pressure tank Install a hose bib on the pressure tank side of the break Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) IF a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. Install backflow prevention valve (as necessary). Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		•
□ Install a hose bib on the pressure tank side of the break □ Drain pressure tank □ Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) □ IF a separate hot water tank is part of the hot water heating system. □ Install a pipe to bypass domestic water system. □ Maintain water in heating system and put anti-freeze in to keep from freezing □ Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler.	☐ Install a hose bib on the pressure tank side of the break ☐ Drain pressure tank ☐ Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) ☐ IF a separate hot water tank is part of the hot water heating system. ☐ Install a pipe to bypass domestic water system. ☐ Maintain water in heating system and put anti-freeze in to keep from freezing ☐ Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. ☐ Install backflow prevention valve (as necessary). ☐ Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		
Drain pressure tank Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) IF a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler.	Place winterization signs on ALL commodes and other plumbing fixtures. 2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) IF a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. Install backflow prevention valve (as necessary). Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		
2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) IF a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler.	2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) IF a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. Install backflow prevention valve (as necessary). Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		•
2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) IF a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler.	2. Heat ON Domestic Plumbing with "Wet" System (Hot Water Baseboard) IF a separate hot water tank is part of the hot water heating system. Install a pipe to bypass domestic water system. Maintain water in heating system and put anti-freeze in to keep from freezing Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. Install backflow prevention valve (as necessary). Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		
IF a separate hot water tank is part of the hot water heating system. ☐ Install a pipe to bypass domestic water system. ☐ Maintain water in heating system and put anti-freeze in to keep from freezing ☐ Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler.	IF a separate hot water tank is part of the hot water heating system. ☐ Install a pipe to bypass domestic water system. ☐ Maintain water in heating system and put anti-freeze in to keep from freezing ☐ Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. ☐ Install backflow prevention valve (as necessary). ☐ Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		Place winterization signs on ALL commodes and other plumbing tixtures.
☐ Install a pipe to bypass domestic water system. ☐ Maintain water in heating system and put anti-freeze in to keep from freezing ☐ Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler.	☐ Install a pipe to bypass domestic water system. ☐ Maintain water in heating system and put anti-freeze in to keep from freezing ☐ Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler. ☐ Install backflow prevention valve (as necessary). ☐ Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)	2. Heat ON	Domestic Plumbing with "Wet" System (Hot Water Baseboard)
	Install backflow prevention valve (as necessary). Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		Install a pipe to bypass domestic water system.
Install backflow prevention valve (as necessary).	Place winterization signs on ALL commodes and other plumbing fixtures. 3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		Add an appropriate amount of Propylene Glycol (non-toxic) to entire hot water system & boiler.
	3. Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		Install backflow prevention valve (as necessary).
Place winterization signs on ALL commodes and other plumbing fixtures.			Place winterization signs on ALL commodes and other plumbing fixtures.
3 Heat ON Domestic Plumbing with "Dry" System (Electric or Forced Air System)		3 Heat ON	Domestic Plumbing with "Dry" System (Electric or Forced Air System)
3. Heat of v Bolitesiae Hallishig with Bly System (Electric of Foreca fin System)	Make sure that all utilities (water, gas/propane/oil/electric/etc.) are operational.	J. Heat OIV	Domestic Framibing with Bry System (Electric of Forecarm System)
Make sure that all utilities (water, gas/propane/oil/electric/etc.) are operational.			Make sure that all utilities (water, gas/propane/oil/electric/etc.) are operational.
	Drain hot water tank and ALL domestic water lines (blow using air pressure).		Drain hot water tank and ALL domestic water lines (blow using air pressure). □ Disconnect and cap red and black wires if electric
	☐ Disconnect and cap red and black wires if electric		Add one quart of Propylene Glycol (non-toxic) to each commode and drain. ☐ Includes laundry traps and drains, showers/tubs, floor and dishwasher drains.
Disconnect and cap red and black wires if electric Add one quart of Propylene Glycol (non-toxic) to each commode and drain.	Add one quart of Propylene Glycol (non-toxic) to each commode and drain.		Place winterization signs on ALL commodes and other plumbing fixtures.
☐ Disconnect and cap red and black wires if electric ☐ Add one quart of Propylene Glycol (non-toxic) to each commode and drain. ☐ Includes laundry traps and drains, showers/tubs, floor and dishwasher drains.	Add one quart of Propylene Glycol (non-toxic) to each commode and drain. □ Includes laundry traps and drains, showers/tubs, floor and dishwasher drains.		Set thermostat at 55° and tape furnace switch to "On" position (if applicable).
Disconnect and cap red and black wires if electric Add one quart of Propylene Glycol (non-toxic) to each commode and drain. Includes laundry traps and drains, showers/tubs, floor and dishwasher drains. Place winterization signs on ALL commodes and other plumbing fixtures.	Add one quart of Propylene Glycol (non-toxic) to each commode and drain. Includes laundry traps and drains, showers/tubs, floor and dishwasher drains. Place winterization signs on ALL commodes and other plumbing fixtures.		Shut off drain humidifier. Leave on ONLY if attached to the boiler.
Disconnect and cap red and black wires if electric Add one quart of Propylene Glycol (non-toxic) to each commode and drain. Includes laundry traps and drains, showers/tubs, floor and dishwasher drains. Place winterization signs on ALL commodes and other plumbing fixtures. Set thermostat at 55° and tape furnace switch to "On" position (if applicable).	Add one quart of Propylene Glycol (non-toxic) to each commode and drain. Includes laundry traps and drains, showers/tubs, floor and dishwasher drains. Place winterization signs on ALL commodes and other plumbing fixtures. Set thermostat at 55° and tape furnace switch to "On" position (if applicable).		Close all storm windows and fireplace dampers. Insulate dryer vent.
L. L			· · · · · · · · · · · · · · · · · · ·
Drain hot water tank and ALL domestic water lines (blow using air pressure).			☐ Disconnect and cap red and black wires if electric
	L.L. Disconnect and can red and black wires it electric		
	☐ Disconnect and cap red and black wires it electric		
	☐ Disconnect and cap red and black wires if electric		Add one quart of Propylene Glycol (non-toxic) to each commode and drain.
	L. L. Hisconnect and can red and black wares it electric		Add one quart of Propylene Glycol (non-toxic) to each commode and drain.
			Add one quart of Propylene Glycol (non-toxic) to each commode and drain.
	☐ Disconnect and cap red and black wires if electric		
☐ Disconnect and cap red and black wires if electric			
☐ Disconnect and cap red and black wires if electric			
Disconnect and cap red and black wires if electric Add one quart of Propylene Glycol (non-toxic) to each commode and drain.	Add one quart of Propylene Glycol (non-toxic) to each commode and drain.		
Disconnect and cap red and black wires if electric Add one quart of Propylene Glycol (non-toxic) to each commode and drain.	Add one quart of Propylene Glycol (non-toxic) to each commode and drain.		Place winterization signs on ALL commodes and other plumbing fixtures.
☐ Disconnect and cap red and black wires if electric ☐ Add one quart of Propylene Glycol (non-toxic) to each commode and drain. ☐ Includes laundry traps and drains, showers/tubs, floor and dishwasher drains.	Add one quart of Propylene Glycol (non-toxic) to each commode and drain. □ Includes laundry traps and drains, showers/tubs, floor and dishwasher drains.		
☐ Disconnect and cap red and black wires if electric ☐ Add one quart of Propylene Glycol (non-toxic) to each commode and drain. ☐ Includes laundry traps and drains, showers/tubs, floor and dishwasher drains.	Add one quart of Propylene Glycol (non-toxic) to each commode and drain. □ Includes laundry traps and drains, showers/tubs, floor and dishwasher drains.		Set thermostat at 55° and tape furnace switch to "On" position (if applicable).
Disconnect and cap red and black wires if electric Add one quart of Propylene Glycol (non-toxic) to each commode and drain. Includes laundry traps and drains, showers/tubs, floor and dishwasher drains. Place winterization signs on ALL commodes and other plumbing fixtures.	Add one quart of Propylene Glycol (non-toxic) to each commode and drain. Includes laundry traps and drains, showers/tubs, floor and dishwasher drains. Place winterization signs on ALL commodes and other plumbing fixtures.		Shut off drain humidifier. Leave on ONLY if attached to the boiler.
Disconnect and cap red and black wires if electric Add one quart of Propylene Glycol (non-toxic) to each commode and drain. Includes laundry traps and drains, showers/tubs, floor and dishwasher drains. Place winterization signs on ALL commodes and other plumbing fixtures. Set thermostat at 55° and tape furnace switch to "On" position (if applicable).	Add one quart of Propylene Glycol (non-toxic) to each commode and drain. Includes laundry traps and drains, showers/tubs, floor and dishwasher drains. Place winterization signs on ALL commodes and other plumbing fixtures. Set thermostat at 55° and tape furnace switch to "On" position (if applicable).		Close all storm windows and fireplace dampers. Insulate dryer vent.
Disconnect and cap red and black wires if electric Add one quart of Propylene Glycol (non-toxic) to each commode and drain. Includes laundry traps and drains, showers/tubs, floor and dishwasher drains. Place winterization signs on ALL commodes and other plumbing fixtures. Set thermostat at 55° and tape furnace switch to "On" position (if applicable). Shut off drain humidifier. Leave on ONLY if attached to the boiler.	Add one quart of Propylene Glycol (non-toxic) to each commode and drain. Includes laundry traps and drains, showers/tubs, floor and dishwasher drains. Place winterization signs on ALL commodes and other plumbing fixtures. Set thermostat at 55° and tape furnace switch to "On" position (if applicable). Shut off drain humidifier. Leave on ONLY if attached to the boiler.		1 1